LIGMAN

Product Spec Sheet


Oulu 5 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample

OUL-80001 - O - W30 - DA - A90291

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19


Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver ND	Remote Driver DI	Remote Driver DA	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · DIMMING TYPE · OPAL DIFFUSER													
☐ OUL-80401 - O - W27	–	96 LED	13	1130	2700K	A++	250	500	250	–	√	√	2.1
☐ OUL-80401 - O - W30	–	96 LED	13	1182	3000K	A++	250	500	250	–	√	√	2.1
☐ OUL-80401 - O - W40	–	96 LED	13	1234	4000K	A++	250	500	250	–	√	√	2.1
☐ OUL-80401 - O - W50	–	96 LED	13	1285	5000K	A++	250	500	250	–	√	√	2.1
☐ OUL-80411 - O - W27	–	192 LED	26	2260	2700K	A++	500	1000	500	–	√	–	3.9
☐ OUL-80411 - O - W30	–	192 LED	26	2364	3000K	A++	500	1000	500	–	√	–	3.9
☐ OUL-80411 - O - W40	–	192 LED	26	2468	4000K	A++	500	1000	500	–	√	–	3.9
☐ OUL-80411 - O - W50	–	192 LED	26	2571	5000K	A++	500	1000	500	–	√	–	3.9
☐ OUL-80421 - O - W27	–	288 LED	39	3391	2700K	A++	750	1500	750	–	√	–	5.7
☐ OUL-80421 - O - W30	–	288 LED	39	9547	3000K	A++	750	1500	750	–	√	–	5.7
☐ OUL-80421 - O - W40	–	288 LED	39	3702	4000K	A++	750	1500	750	–	√	–	5.7
☐ OUL-80421 - O - W50	–	288 LED	39	3856	5000K	A++	750	1500	750	–	√	–	5.7
☐ OUL-80431 - O - W27	–	384 LED	52	4521	2700K	A++	1000	2000	1000	–	√	–	7.7
☐ OUL-80431 - O - W30	–	384 LED	52	4729	3000K	A++	1000	2000	1000	–	√	–	7.7
☐ OUL-80431 - O - W40	–	384 LED	52	4936	4000K	A++	1000	2000	1000	–	√	–	7.7
☐ OUL-80431 - O - W50	–	384 LED	52	5141	5000K	A++	1000	2000	1000	–	√	–	7.7

Optional diffuser



☐ (- O)
Opal diffuser
UGR <19

Dimming Type

☐ ND ☐ DI ☐ DA

Colour Code

☐ - 01 Black RAL 9011

☐ - 03 White RAL 9003

☐ - 05 Matt Silver RAL 9006

RESET

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet

Oulu 5 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

Accessory



☐ Continuous coupler bracket (A81781)




☐ Bracket For Ceilings (A81381)

Accessory For Wireless Bluetooth




☐ Wireless Bluetooth (A90291)



☐ xPress Wireless switch (A90591)

Photometric



• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 5 RGBW DMX

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-80404 - O - RGBW40 - 81381

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
W40 - Neutral white 4000K
RGBW

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · BGBW DMX · OPAL DIFFUSER											
◯ OUL-80404 - O - RGBW	—	192 LED	13	432	RGBW40	A++	250	500	250	√	1.9
◯ OUL-80414 - O - RGBW	—	480 LED	27	956	RGBW40	A++	500	1000	500	√	3.7
◯ OUL-80424 - O - RGBW	—	768 LED	43	1434	RGBW40	A++	750	1500	750	√	5.4
◯ OUL-80434 - O - RGBW	—	960 LED	54	1911	RGBW40	A++	1000	2000	1000	√	7.3

Colour Temperature

◯ RGBW40

DMX Accessory



◯ SLESA-U9
(A60491)



◯ SLESA-UE7
(A60691)



◯ STICK-KE1
(A60791)

Colour Code

◯ - 01 Black RAL 9011
◯ - 03 White RAL 9003
◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 5 RGBW Wireless Bluetooth

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-80403 - O - RGBW40 - A81381

- OUL-80403 — Model No.
- O — Diffuser
- RGBW40 — Colour
- A81381 — Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
W40 - Neutral white 4000K
RGBW

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · BGBW WIRELESS BLUETOOTH · OPAL DIFFUSER											
◯ OUL-80403 - O - RGBW	—	192 LED	13	432	RGBW40	A++	250	500	250	√	1.9
◯ OUL-80413 - O - RGBW	—	480 LED	27	956	RGBW40	A++	500	1000	500	√	3.7
◯ OUL-80423 - O - RGBW	—	768 LED	43	1434	RGBW40	A++	750	1500	750	√	5.4
◯ OUL-80433 - O - RGBW	—	960 LED	54	1911	RGBW40	A++	1000	2000	1000	√	7.3

Colour Temperature

◯ RGBW40

Accessory For Wireless Bluetooth



◯ xPress
Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011
◯ - 03 White RAL 9003
◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 5 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-80402 - O - TUW - A90291

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-80402 - O - TUW	–	144 LED	13	1234	TUW	A++	250	500	250	√	1.9
◯ OUL-80412 - O - TUW	–	384 LED	27	2732	TUW	A++	500	1000	500	-	3.9
◯ OUL-80422 - O - TUW	–	576 LED	40	4096	TUW	A++	750	1500	750	-	5.7
◯ OUL-80432 - O - TUW	–	768 LED	54	5460	TUW	A++	1000	2000	1000	-	7.7

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)



◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

LIGMAN

Product Spec Sheet


Oulu 5 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample

OUL-80501 - O - W30 - DA - A90291

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver ND	Remote Driver DI	Remote Driver DA	Weight kg
SURFACE CEILING MOUNTED · UP-DOWN LIGHT · DIMMING TYPE · OPAL DIFFUSER													
◯ OUL-80501 - O - W27	96 LED	96 LED	25	2389	2700K	A++	250	500	250	–	√	√	2.6
◯ OUL-80501 - O - W30	96 LED	96 LED	25	2492	3000K	A++	250	500	250	–	√	√	2.6
◯ OUL-80501 - O - W40	96 LED	96 LED	25	2596	4000K	A++	250	500	250	–	√	√	2.6
◯ OUL-80501 - O - W50	96 LED	96 LED	25	2704	5000K	A++	250	500	250	–	√	√	2.6
◯ OUL-80511 - O - W27	192 LED	192 LED	50	4756	2700K	A++	500	1000	500	–	√	–	4.8
◯ OUL-80511 - O - W30	192 LED	192 LED	50	4974	3000K	A++	500	1000	500	–	√	–	4.8
◯ OUL-80511 - O - W40	192 LED	192 LED	50	5192	4000K	A++	500	1000	500	–	√	–	4.8
◯ OUL-80511 - O - W50	192 LED	192 LED	50	5408	5000K	A++	500	1000	500	–	√	–	4.8
◯ OUL-80521 - O - W27	288 LED	288 LED	74	7134	2700K	A++	750	1500	750	–	√	–	7.1
◯ OUL-80521 - O - W30	288 LED	288 LED	74	7461	3000K	A++	750	1500	750	–	√	–	7.1
◯ OUL-80521 - O - W40	288 LED	288 LED	74	7788	4000K	A++	750	1500	750	–	√	–	7.1
◯ OUL-80521 - O - W50	288 LED	288 LED	74	8112	5000K	A++	750	1500	750	–	√	–	7.1
◯ OUL-80531 - O - W27	384 LED	384 LED	98	9512	2700K	A++	1000	2000	1000	–	√	–	9.3
◯ OUL-80531 - O - W30	384 LED	384 LED	98	9948	3000K	A++	1000	2000	1000	–	√	–	9.3
◯ OUL-80531 - O - W40	384 LED	384 LED	98	10384	4000K	A++	1000	2000	1000	–	√	–	9.3
◯ OUL-80531 - O - W50	384 LED	384 LED	98	10816	5000K	A++	1000	2000	1000	–	√	–	9.3

Optional diffuser



◯ (- O)
Opal diffuser
UGR <19

Dimming Type

◯ ND ◯ DI ◯ DA

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet

Oulu 5 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

Accessory




◯ Continuous coupler bracket (A81781)

Accessory For Wireless Bluetooth




◯ Wireless Bluetooth (A90291)



◯ xPress Wireless switch (A90591)

Photometric



• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 5 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample


OUL-80502 - O - TUW - A90291

- O – Diffuser
- TUW – Colour
- A90291 – Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	Lamp UP	Lamp DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · UP-DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-80502 - O - TUW	144 LED	144 LED	26	2596	TUW	A++	250	500	250	√	2.5
◯ OUL-80512 - O - TUW	384 LED	384 LED	54	5464	TUW	A++	500	1000	500	√	4.5
◯ OUL-80522 - O - TUW	576 LED	576 LED	80	8192	TUW	A++	750	1500	750	-	7.1
◯ OUL-80532 - O - TUW	768 LED	768 LED	108	10920	TUW	A++	1000	2000	1000	-	9.3

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)



◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 5 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample


OUL-80502 - O - TUW - A90291

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19

Product Code

Model No.	Lamp UP	Lamp DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · UP-DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-80502 - O - WTU	144 LED	144 LED	26	2596	WTU	A++	250	500	250	√	2.5
◯ OUL-80512 - O - WTU	384 LED	384 LED	54	5464	WTU	A++	500	1000	500	√	4.5
◯ OUL-80522 - O - WTU	576 LED	576 LED	80	8192	WTU	A++	750	1500	750	-	7.1
◯ OUL-80532 - O - WTU	768 LED	768 LED	108	10920	WTU	A++	1000	2000	1000	-	9.3


Colour Temperature

◯ RGBW40

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)



◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 6 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample

OUL-80601 - O - W30 - DA - A90291

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19


Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver ND	Remote Driver DI	Remote Driver DA	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · DIMMING TYPE · OPAL DIFFUSER														
◯ OUL-80601 - O - W27	–	96 LED	12	1153	2700K	A++	500	500	500	–	√	–	–	2.2
◯ OUL-80601 - O - W30	–	96 LED	12	1204	3000K	A++	500	500	500	–	√	–	–	2.2
◯ OUL-80601 - O - W40	–	96 LED	12	1254	4000K	A++	500	500	500	–	√	–	–	2.2
◯ OUL-80601 - O - W50	–	96 LED	12	1306	5000K	A++	500	500	500	–	√	–	–	2.2
◯ OUL-80611 - O - W27	–	144 LED	18	1772	2700K	A++	750	750	750	–	√	–	–	3.1
◯ OUL-80611 - O - W30	–	144 LED	18	1849	3000K	A++	750	750	750	–	√	–	–	3.1
◯ OUL-80611 - O - W40	–	144 LED	18	1926	4000K	A++	750	750	750	–	√	–	–	3.1
◯ OUL-80611 - O - W50	–	144 LED	18	2007	5000K	A++	750	750	750	–	√	–	–	3.1
◯ OUL-80621 - O - W27	–	192 LED	25	2297	2700K	A++	1000	1000	1000	–	√	–	–	4.2
◯ OUL-80621 - O - W30	–	192 LED	25	2403	3000K	A++	1000	1000	1000	–	√	–	–	4.2
◯ OUL-80621 - O - W40	–	192 LED	25	2508	4000K	A++	1000	1000	1000	–	√	–	–	4.2
◯ OUL-80621 - O - W50	–	192 LED	25	2612	5000K	A++	1000	1000	1000	–	√	–	–	4.2
◯ OUL-80631 - O - W27	–	240 LED	31	2872	2700K	A++	1250	1250	1250	–	√	–	–	5.0
◯ OUL-80631 - O - W30	–	240 LED	31	3003	3000K	A++	1250	1250	1250	–	√	–	–	5.0
◯ OUL-80631 - O - W40	–	240 LED	31	3135	4000K	A++	1250	1250	1250	–	√	–	–	5.0
◯ OUL-80631 - O - W50	–	240 LED	31	3265	5000K	A++	1250	1250	1250	–	√	–	–	5.0

Optional diffuser



◯ (- O)
Opal diffuser
UGR <19

Dimming Type

◯ ND ◯ DI ◯ DA

Colour Code

◯ - 01 Black RAL 9011
◯ - 03 White RAL 9003
◯ - 05 Matt Silver RAL 9006

RESET

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet

Oulu 6 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

Accessory



◯ Continuous coupler bracket (A81781)




◯ Bracket For Ceilings (A81381)

Accessory For Wireless Bluetooth





◯ Wireless Bluetooth (A90291)



◯ xPress Wireless switch (A90591)

Photometric





• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

LIGMAN

Product Spec Sheet


Oulu 6 RGBW DMX

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-80604 - O - RGBW40 - A81381

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
W40 - Neutral white 4000K
RGBW

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · BGBW DMX · OPAL DIFFUSER											
◯ OUL-80604 - O - RGBW	–	240 LED	13	439	RGBW40	A++	500	500	500	√	2.0
◯ OUL-80614 - O - RGBW	–	384 LED	21	674	RGBW40	A++	750	750	750	√	2.8
◯ OUL-80624 - O - RGBW	–	480 LED	26	956	RGBW40	A++	1000	1000	1000	√	3.8
◯ OUL-80634 - O - RGBW	–	672 LED	37	1195	RGBW40	A++	1250	1250	1250	√	4.7

Colour Temperature

◯ RGBW40

DMX Accessory



◯ SLESA-U9
(A60491)



◯ SLESA-UE7
(A60691)



◯ STICK-KE1
(A60791)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

LIGMAN

Product Spec Sheet


Oulu 6 RGBW Wireless Bluetooth

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-80603 - O - RGBW40 - A81381

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
W40 - Neutral white 4000K
RGBW

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · BGBW WIRELESS BLUETOOTH · OPAL DIFFUSER											
◯ OUL-80603 - O - RGBW	–	240 LED	13	439	RGBW40	A++	500	500	500	√	2.0
◯ OUL-80613 - O - RGBW	–	384 LED	21	674	RGBW40	A++	750	750	750	√	2.8
◯ OUL-80623 - O - RGBW	–	480 LED	26	956	RGBW40	A++	1000	1000	1000	√	3.8
◯ OUL-80633 - O - RGBW	–	672 LED	37	1195	RGBW40	A++	1250	1250	1250	√	4.7

Colour Temperature

◯ RGBW40

Accessory For Wireless Bluetooth



◯ xPress
Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 6 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-80602 - O - TUW - A90291

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-80602 - O - TUW	–	192 LED	13	1254	TUW	A++	500	500	500	-	2.2
◯ OUL-80612 - O - TUW	–	288 LED	20	1926	TUW	A++	750	750	750	-	3.1
◯ OUL-80622 - O - TUW	–	384 LED	26	2730	TUW	A++	1000	1000	1000	-	4.2
◯ OUL-80632 - O - TUW	–	480 LED	33	3414	TUW	A++	1250	1250	1250	-	5.0

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)



◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

LIGMAN

Product Spec Sheet


Oulu 6 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample

OUL-80701 - O - W30 - DA - A90291

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver ND	Remote Driver DI	Remote Driver DA	Weight kg
SURFACE CEILING MOUNTED · UP-DOWN LIGHT · DIMMING TYPE · OPAL DIFFUSER													
◯ OUL-80701 - O - W27	96 LED	96 LED	25	2404	2700K	A++	500	500	500	–	√	–	2.8
◯ OUL-80701 - O - W30	96 LED	96 LED	25	2508	3000K	A++	500	500	500	–	√	–	2.8
◯ OUL-80701 - O - W40	96 LED	96 LED	25	2613	4000K	A++	500	500	500	–	√	–	2.8
◯ OUL-80701 - O - W50	96 LED	96 LED	25	2721	5000K	A++	500	500	500	–	√	–	2.8
◯ OUL-80711 - O - W27	144 LED	144 LED	37	3690	2700K	A++	750	750	750	–	√	–	3.9
◯ OUL-80711 - O - W30	144 LED	144 LED	37	3851	3000K	A++	750	750	750	–	√	–	3.9
◯ OUL-80711 - O - W40	144 LED	144 LED	37	4011	4000K	A++	750	750	750	–	√	–	3.9
◯ OUL-80711 - O - W50	144 LED	144 LED	37	4178	5000K	A++	750	750	750	–	√	–	3.9
◯ OUL-80721 - O - W27	192 LED	192 LED	49	4787	2700K	A++	1000	1000	1000	–	√	–	5.2
◯ OUL-80721 - O - W30	192 LED	192 LED	49	5007	3000K	A++	1000	1000	1000	–	√	–	5.2
◯ OUL-80721 - O - W40	192 LED	192 LED	49	5226	4000K	A++	1000	1000	1000	–	√	–	5.2
◯ OUL-80721 - O - W50	192 LED	192 LED	49	5443	5000K	A++	1000	1000	1000	–	√	–	5.2
◯ OUL-80731 - O - W27	240 LED	240 LED	62	5984	2700K	A++	1250	1250	1250	–	√	–	6.2
◯ OUL-80731 - O - W30	240 LED	240 LED	62	6258	3000K	A++	1250	1250	1250	–	√	–	6.2
◯ OUL-80731 - O - W40	240 LED	240 LED	62	6533	4000K	A++	1250	1250	1250	–	√	–	6.2
◯ OUL-80731 - O - W50	240 LED	240 LED	62	6804	5000K	A++	1250	1250	1250	–	√	–	6.2

Optional diffuser



◯ (- O)
Opal diffuser
UGR <19

Dimming Type

◯ ND ◯ DI ◯ DA

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet

Oulu 6 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

Accessory




◯ Continuous coupler bracket (A81781)

Accessory For Wireless Bluetooth





◯ Wireless Bluetooth (A90291)



◯ xPress Wireless switch (A90591)

Photometric





• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 6 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample


OUL-80702 - O - TUW - A90291

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · UP-DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-80702 - O - TUW	192 LED	192 LED	25	2613	TUW	A++	500	500	500	-	2.8
◯ OUL-80712 - O - TUW	288 LED	288 LED	37	4011	TUW	A++	750	750	750	-	3.9
◯ OUL-80722 - O - TUW	384 LED	384 LED	52	5460	TUW	A++	1000	1000	1000	√	4.6
◯ OUL-80732 - O - TUW	480 LED	480 LED	66	6828	TUW	A++	1250	1250	1250	√	5.7

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)



◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 7 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample

OUL-80001 - O - W30 - DA - A90291

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19


Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver ND	Remote Driver DI	Remote Driver DA	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · DIMMING TYPE · **OPAL** DIFFUSER													
◯ OUL-80801 - O - W27	–	96 LED	12	1157	2700K	A++	1000	335	707	–	√	–	2.2
◯ OUL-80801 - O - W30	–	96 LED	12	1208	3000K	A++	1000	335	707	–	√	–	2.2
◯ OUL-80801 - O - W40	–	96 LED	12	1258	4000K	A++	1000	335	707	–	√	–	2.2
◯ OUL-80801 - O - W50	–	96 LED	12	1310	5000K	A++	1000	335	707	–	√	–	2.2
◯ OUL-80811 - O - W27	–	120 LED	16	1469	2700K	A++	1250	408	883	–	√	–	2.8
◯ OUL-80811 - O - W30	–	120 LED	16	1533	3000K	A++	1250	408	883	–	√	–	2.8
◯ OUL-80811 - O - W40	–	120 LED	16	1597	4000K	A++	1250	408	883	–	√	–	2.8
◯ OUL-80811 - O - W50	–	120 LED	16	1663	5000K	A++	1250	408	883	–	√	–	2.8
◯ OUL-80821 - O - W27	–	144 LED	18	1594	2700K	A++	1500	482	1060	–	√	–	3.2
◯ OUL-80821 - O - W30	–	144 LED	18	1663	3000K	A++	1500	482	1060	–	√	–	3.2
◯ OUL-80821 - O - W40	–	144 LED	18	1732	4000K	A++	1500	482	1060	–	√	–	3.2
◯ OUL-80821 - O - W50	–	144 LED	18	1804	5000K	A++	1500	482	1060	–	√	–	3.2
◯ OUL-80831 - O - W27	–	192 LED	24	2314	2700K	A++	2000	628	1414	–	√	–	4.2
◯ OUL-80831 - O - W30	–	192 LED	24	2416	3000K	A++	2000	628	1414	–	√	–	4.2
◯ OUL-80831 - O - W40	–	192 LED	24	2516	4000K	A++	2000	628	1414	–	√	–	4.2
◯ OUL-80831 - O - W50	–	192 LED	24	2620	5000K	A++	2000	628	1414	–	√	–	4.2
◯ OUL-80841 - O - W27	–	240 LED	30	2893	2700K	A++	2500	774	1768	–	√	–	5.0
◯ OUL-80841 - O - W30	–	240 LED	30	3020	3000K	A++	2500	774	1768	–	√	–	5.0
◯ OUL-80841 - O - W40	–	240 LED	30	3145	4000K	A++	2500	774	1768	–	√	–	5.0
◯ OUL-80841 - O - W50	–	240 LED	30	3275	5000K	A++	2500	774	1768	–	√	–	5.0

Optional diffuser



◯ (- O)
Opal diffuser
UGR <19

Dimming Type

◯ ND ◯ DI ◯ DA

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet

Oulu 7 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

Accessory



◯ Continuous coupler bracket (A81781)




◯ Bracket For Ceilings (A81381)

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth (A90291)



◯ xPress Wireless switch (A90591)

Colour Code


◯ - 01 Black RAL 9011


◯ - 03 White RAL 9003


◯ - 05 Matt Silver RAL 9006

RESET

Photometric







• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 7 RGBW DMX

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-80804 - O - RGBW40 - A81381

- OUL-80804 — Model No.
- O — Diffuser
- RGBW40 — Colour
- A81381 — Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
W40 - Neutral white 4000K
RGBW

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · BGBW DMX· OPAL DIFFUSER											
◯ OUL-80804 - O - RGBW	—	240 LED	13	440	RGBW40	A++	1000	335	707	√	2.0
◯ OUL-80814 - O - RGBW	—	336 LED	19	559	RGBW40	A++	1250	408	883	√	2.5
◯ OUL-80824 - O - RGBW	—	384 LED	21	606	RGBW40	A++	1500	482	1060	√	2.8
◯ OUL-80834 - O - RGBW	—	480 LED	27	956	RGBW40	A++	2000	628	1414	√	3.8
◯ OUL-80844 - O - RGBW	—	688 LED	37	1195	RGBW40	A++	2500	774	1768	√	4.8

Colour Temperature

◯ RGBW40

DMX Accessory



◯ SLESA-U9
(A60491)



◯ SLESA-UE7
(A60691)



◯ STICK-KE1
(A60791)

Colour Code

◯ - 01 Black RAL 9011
◯ - 03 White RAL 9003
◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 7 RGBW Wireless Bluetooth

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample

OUL-80803 - O - RGBW40 - A81381

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
W40 - Neutral white 4000K
RGBW

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · BGBW WIRELESS BLUETOOTH · OPAL DIFFUSER											
◯ OUL-80803 - O - RGBW	–	240 LED	13	440	RGBW40	A++	1000	335	707	√	2.0
◯ OUL-80813 - O - RGBW	–	336 LED	19	559	RGBW40	A++	1250	408	883	√	2.5
◯ OUL-80823 - O - RGBW	–	384 LED	21	606	RGBW40	A++	1500	482	1060	√	2.8
◯ OUL-80833 - O - RGBW	–	480 LED	27	956	RGBW40	A++	2000	628	1414	√	3.8
◯ OUL-80843 - O - RGBW	–	688 LED	37	1195	RGBW 40	A++	2500	774	1768	√	4.8

Colour Code


◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Lens diffuser




◯ (- O) Opal diffuser UGR <19

Colour Temperature

◯ RGBW40

Accessory For Wireless Bluetooth



◯ xPress Wireless switch (A90591)

Accessory



◯ Bracket For Ceilings (A81381)



◯ Continuous coupler bracket (A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 7 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-80802 - O - TUW - A90291

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-80802 - O - TUW	—	192 LED	13	1258	TUW	A++	1000	335	707	-	2.2
◯ OUL-80812 - O - TUW	—	240 LED	17	1597	TUW	A++	1250	408	883	-	2.8
◯ OUL-80822 - O - TUW	—	288 LED	20	1732	TUW	A++	1500	482	1060	-	3.2
◯ OUL-80832 - O - TUW	—	384 LED	27	2730	TUW	A++	2000	628	1414	-	4.2
◯ OUL-80842 - O - TUW	—	480 LED	33	3414	TUW	A++	2500	774	1768	-	5.0

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)



◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 7 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample

OUL-80901 - O - W30 - DA - A90291

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19


Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver ND	Remote Driver DI	Remote Driver DA	Weight kg
SURFACE CEILING MOUNTED · UP-DOWN LIGHT · DIMMING TYPE · OPAL DIFFUSER													
◯ OUL-80901 - O - W27	96 LED	96 LED	25	2408	2700K	A++	1000	335	707	–	√	–	2.9
◯ OUL-80901 - O - W30	96 LED	96 LED	25	2513	3000K	A++	1000	335	707	–	√	–	2.9
◯ OUL-80901 - O - W40	96 LED	96 LED	25	2617	4000K	A++	1000	335	707	–	√	–	2.9
◯ OUL-80901 - O - W50	96 LED	96 LED	25	2726	5000K	A++	1000	335	707	–	√	–	2.9
◯ OUL-80911 - O - W27	120 LED	120 LED	31	3047	2700K	A++	1250	408	883	–	√	–	3.5
◯ OUL-80911 - O - W30	120 LED	120 LED	31	3179	3000K	A++	1250	408	883	–	√	–	3.5
◯ OUL-80911 - O - W40	120 LED	120 LED	31	3311	4000K	A++	1250	408	883	–	√	–	3.5
◯ OUL-80911 - O - W50	120 LED	120 LED	31	3449	5000K	A++	1250	408	883	–	√	–	3.5
◯ OUL-80921 - O - W27	144 LED	144 LED	37	3491	2700K	A++	1500	482	1060	–	√	–	4.0
◯ OUL-80921 - O - W30	144 LED	144 LED	37	3643	3000K	A++	1500	482	1060	–	√	–	4.0
◯ OUL-80921 - O - W40	144 LED	144 LED	37	3795	4000K	A++	1500	482	1060	–	√	–	4.0
◯ OUL-80921 - O - W50	144 LED	144 LED	37	3953	5000K	A++	1500	482	1060	–	√	–	4.0
◯ OUL-80931 - O - W27	192 LED	192 LED	49	4794	2700K	A++	2000	628	1414	–	√	–	5.3
◯ OUL-80931 - O - W30	192 LED	192 LED	49	5014	3000K	A++	2000	628	1414	–	√	–	5.3
◯ OUL-80931 - O - W40	192 LED	192 LED	49	5234	4000K	A++	2000	628	1414	–	√	–	5.3
◯ OUL-80931 - O - W50	192 LED	192 LED	49	5452	5000K	A++	2000	628	1414	–	√	–	5.3
◯ OUL-80941 - O - W27	240 LED	240 LED	62	5993	2700K	A++	2500	774	1768	–	√	–	6.2
◯ OUL-80941 - O - W30	240 LED	240 LED	62	6268	3000K	A++	2500	774	1768	–	√	–	6.2
◯ OUL-80941 - O - W40	240 LED	240 LED	62	6543	4000K	A++	2500	774	1768	–	√	–	6.2
◯ OUL-80941 - O - W50	240 LED	240 LED	62	6815	5000K	A++	2500	774	1768	–	√	–	6.2

Optional diffuser



◯ (- O)
Opal diffuser
UGR <19

Dimming Type

◯ ND ◯ DI ◯ DA

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet

Oulu 7 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

Accessory




◯ Continuous coupler bracket (A81781)

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth (A90291)



◯ xPress Wireless switch (A90591)

Colour Code


◯ - 01 Black RAL 9011


◯ - 03 White RAL 9003


◯ - 05 Matt Silver RAL 9006

RESET

Photometric







• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 7 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample

OUL-80902 - O - TUW - A90291

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · UP-DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-80902 - O - TUW	192 LED	192 LED	25	2617	TUW	A++	1000	335	707	√	2.5
◯ OUL-80912 - O - TUW	240 LED	240 LED	31	3311	TUW	A++	1250	408	883	√	3.1
◯ OUL-80922 - O - TUW	288 LED	288 LED	37	3795	TUW	A++	1500	482	1060	√	3.6
◯ OUL-80932 - O - TUW	384 LED	384 LED	52	5460	TUW	A++	2000	628	1414	-	4.6
◯ OUL-80942 - O - TUW	480 LED	480 LED	66	6828	TUW	A++	2500	774	1768	-	5.7

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)



◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 8 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample

OUL-81011 - O - W30 - DA - A90291

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19


Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver ND	Remote Driver DI	Remote Driver DA	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · DIMMING TYPE · OPAL DIFFUSER													
◯ OUL-81011 - O - W27	–	96 LED	13	1210	2700K	A++	2000	208	765	–	√	–	2.3
◯ OUL-81011 - O - W30	–	96 LED	13	1266	3000K	A++	2000	208	765	–	√	–	2.3
◯ OUL-81011 - O - W40	–	96 LED	13	1321	4000K	A++	2000	208	765	–	√	–	2.3
◯ OUL-81011 - O - W50	–	96 LED	13	1376	5000K	A++	2000	208	765	–	√	–	2.3
◯ OUL-81021 - O - W27	–	120 LED	16	1427	2700K	A++	2500	284	1148	–	√	–	2.8
◯ OUL-81021 - O - W30	–	120 LED	16	1492	3000K	A++	2500	284	1148	–	√	–	2.8
◯ OUL-81021 - O - W40	–	120 LED	16	1558	4000K	A++	2500	284	1148	–	√	–	2.8
◯ OUL-81021 - O - W50	–	120 LED	16	1623	5000K	A++	2500	284	1148	–	√	–	2.8

Optional diffuser



◯ (- O)
Opal diffuser
UGR <19

Dimming Type

◯ ND ◯ DI ◯ DA

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet

Oulu 8 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

Accessory



◯ Continuous coupler bracket (A81781)




◯ Bracket For Ceilings (A81381)

Accessory For Wireless Bluetooth





◯ Wireless Bluetooth (A90291)



◯ xPress Wireless switch (A90591)

Photometric





• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 8 RGBW DMX

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample

OUL-81014 - O - RGBW40 - A81381

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
W40 - Neutral white 4000K
RGBW

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · RGBW DMX · OPAL DIFFUSER											
◯ OUL-81014 - O - RGBW	—	240 LED	13	462	RGBW40	A++	2000	208	765	√	2.0
◯ OUL-81024 - O - RGBW	—	344 LED	19	545	RGBW40	A++	2500	284	1148	√	2.5

Colour Code


◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19

Colour Temperature

◯ RGBW40

DMX Accessory



◯ SLESA-U9
(A60491)



◯ SLESA-UE7
(A60691)



◯ STICK-KE1
(A60791)

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 8 RGBW Wireless Bluetooth

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-81013 - O - RGBW40 - A81381

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
W40 - Neutral white 4000K
RGBW

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · RGBW WIRELESS BLUETOOTH · OPAL DIFFUSER											
◯ OUL-81013 - O - RGBW	—	240 LED	13	462	RGBW40	A++	2000	208	765	√	2.0
◯ OUL-81023 - O - RGBW	—	344 LED	19	545	RGBW40	A++	2500	284	1148	√	2.5

Colour Temperature

◯ RGBW40

Accessory For Wireless Bluetooth



◯ xPress
Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 8 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Down light

Ordering guide sample


OUL-81012 - O - TUW - A90291

Diffuser | Colour | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-81012 - O - TUW	—	192 LED	13	1321	TUW	A++	2000	208	765	√	2.0
◯ OUL-81022 - O - TUW	—	240 LED	16	1558	TUW	A++	2500	284	1148	√	2.5

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)



◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.

LIGMAN

Product Spec Sheet


Oulu 8 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample

OUL-80501 - O - W30 - DA - A90291

Diffuser | Colour | Dim Type | Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Dimming Type
ND – Non dimmable
DI – 1-10V dimmable
DA – DALI dimmable

Colour Temperature
W27 – Warm 2700K
W30 – Warm white 3000K
W40 – Neutral white 4000K
W50 – Cool white 5000K

Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver ND	Remote Driver DI	Remote Driver DA	Weight kg
UP-DOWNLIGHT · 22.5°													
DIMMING TYPE													
◯ OUL-81111 - O - W27	96 LED	96 LED	26	2474	2700K	A++	2000	208	765	–	√	–	2.8
◯ OUL-81111 - O - W30	96 LED	96 LED	26	2588	3000K	A++	2000	208	765	–	√	–	2.8
◯ OUL-81111 - O - W40	96 LED	96 LED	26	2701	4000K	A++	2000	208	765	–	√	–	2.8
◯ OUL-81111 - O - W50	96 LED	96 LED	26	2814	5000K	A++	2000	208	765	–	√	–	2.8
◯ OUL-81121 - O - W27	120 LED	120 LED	31	3012	2700K	A++	2500	284	1148	–	√	–	3.5
◯ OUL-81121 - O - W30	120 LED	120 LED	31	3150	3000K	A++	2500	284	1148	–	√	–	3.5
◯ OUL-81121 - O - W40	120 LED	120 LED	31	3288	4000K	A++	2500	284	1148	–	√	–	3.5
◯ OUL-81121 - O - W50	120 LED	120 LED	31	3425	5000K	A++	2500	284	1148	–	√	–	3.5

Optional diffuser



◯ (- O)
Opal diffuser
UGR <19

Dimming Type

◯ ND ◯ DI ◯ DA

Colour Code

◯ - 01 Black RAL 9011

◯ - 03 White RAL 9003

◯ - 05 Matt Silver RAL 9006

RESET

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet

Oulu 8 Dimming Type

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

Accessory




◯ Continuous coupler bracket (A81781)

Accessory For Wireless Bluetooth





◯ Wireless Bluetooth (A90291)



◯ xPress Wireless switch (A90591)

Photometric





• Installation manual available online at www.ligman.com.
• Luminous flux and system power are rated from absolute photometry according to LM-79-08 standard for LED luminaire.
• Photometric diagram for standard non-accessory, please consult the factory in case accessory option.

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD | United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 | sales.uk@ligman.com

Technical amendments reserved.

Product Spec Sheet


Oulu 8 Tunable White

Surface ceiling luminaires

Project :	Location :	Type :	Quantity :
Note :			

IP20





Luminaire Structure

Unique family of curved extruded linear fixtures
Release your imagination, designing spaces with the multiple curves in the Oulo range

Light Symbol



Up - Down light

Ordering guide sample


OUL-81112 - O - TUW - A90291

- OUL-81112 — Diffuser
- O — Colour
- A90291 — Accessory 1

Diffuser for light output control
O – Opal diffuser UGR <19

Colour Temperature
TUW – Tunable white
2700K – 6500K

Lens diffuser



◯ (- O)
Opal diffuser
UGR <19


Product Code

Model No.	No. LED UP	No. LED DOWN	System Power W	Lumen lm	Colour	EEC	Dimension R	Dimension L1	Dimension L2	Remote Driver	Weight kg
SURFACE CEILING MOUNTED · UP-DOWN LIGHT · TUNABLE WHITE · OPAL DIFFUSER											
◯ OUL-81112 - O - W27	192 LED	192 LED	26	2701	2700K	A++	2000	208	765	√	2.4
◯ OUL-81122 - O - W30	240 LED	240 LED	31	3288	3000K	A++	2500	284	1148	√	3.0

Accessory For Wireless Bluetooth



◯ Wireless Bluetooth
(A90291)




◯ xPress Wireless switch
(A90591)

Colour Code

◯ - 01	◯ - 03	◯ - 05	
Black RAL 9011	White RAL 9003	Matt Silver RAL 9006	RESET

Accessory



◯ Bracket For Ceilings
(A81381)



◯ Continuous coupler bracket
(A81781)

HEADQUARTERS EUROPE

Ligman Europe s.r.o.
VGP Park Ústí nad Labem, P2 | Přestanov 120 | 40317 Přestanov | Czech Republic | Tel. +420 477 07 1500 | sales.cz@ligman.com

www.ligman.com

HEADQUARTERS THAILAND

Ligman Lighting Co.,Ltd.
17/2 | Moo 4 | Monthong | Bangnampreaw | Chachoengsao 24150 | Thailand | Tel : +66 (2) 7339140 | info@ligman.com

Ligman Ltd.
Victory Way | Crossways | Dartford DA2 6QD |
United Kingdom | Tel +66 2 733 9140 | Fax +66 2 733 9153 |
sales.uk@ligman.com

Technical amendments reserved.